according to Regulation (EC) No 1907/2006

#### **ADDINOL RACING 4T 15W-50**

Revision date: 30.09.2020 Product code: 721058 Page 1 of 8

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

ADDINOL RACING 4T 15W-50

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Motor oil.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Specialised Products (Western) Limited
Street: 76 Cobham Road, Ferndown Industrial Estate,

Place: GB-BH21 7RN Wimborne, Dorset

Telephone: +44 1202 891393 Telefax: +44 1202 876908

e-mail: sales@specialisedproducts.co.uk
Internet: http://specialisedproducts.co.uk

1.4. Emergency telephone +44 1202 891393 - This number is serviced during office hours.

number:

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Regulation (EC) No. 1272/2008

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

# 2.2. Label elements

### Regulation (EC) No. 1272/2008

# **Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

### **Precautionary statements**

P273 Avoid release to the environment.

P501 Dispose of contents/container to a waste disposal system.

### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

according to Regulation (EC) No 1907/2006

### **ADDINOL RACING 4T 15W-50**

Revision date: 30.09.2020 Product code: 721058 Page 2 of 8

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification	•	•	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			60 - < 80 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			
	Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased			1 - < 2.5 %
	701-251-5			
	Aquatic Chronic 4; H413			
74499-35-7	phenol, (tetrapropenyl) derivatives			< 0.1 %
	-	604-092-00-9		
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 10); H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

### **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

# After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

# After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

# 4.2. Most important symptoms and effects, both acute and delayed

No information available.

# 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### **SECTION 5: Firefighting measures**

according to Regulation (EC) No 1907/2006

#### **ADDINOL RACING 4T 15W-50**

Revision date: 30.09.2020 Product code: 721058 Page 3 of 8

### 5.1. Extinguishing media

### Suitable extinguishing media

Atomized water. Foam. Extinguishing powder. Carbon dioxide (CO2).

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

# 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

# 6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eye and clothing.

# Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

### Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

### 7.3. Specific end use(s)

Motor oil.

according to Regulation (EC) No 1907/2006

### **ADDINOL RACING 4T 15W-50**

Revision date: 30.09.2020 Product code: 721058 Page 4 of 8

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

### 8.2. Exposure controls





#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

#### Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

### **Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

# Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: yellow - brown Odour: characteristic

Test method

pH-Value: No data available

Changes in the physical state

according to Regulation (EC) No 1907/2006

# **ADDINOL RACING 4T 15W-50**

Revision date: 30.09.2020 Product code: 721058 Page 5 of 8

Melting point:

No data available
Initial boiling point and boiling range:

No data available

Pour point: -39 °C ASTM D 7346
Flash point: 251 °C DIN EN ISO 2592

Flammability

Solid: No data available
Gas: No data available

**Explosive properties** 

No data available

Lower explosion limits:

Upper explosion limits:

No data available

Ignition temperature:

No data available

**Auto-ignition temperature** 

Solid: No data available
Gas: No data available
Decomposition temperature: No data available

**Oxidizing properties** 

No data available

Vapour pressure: No data available

Density (at 15 °C): 0,867 g/cm³ DIN 51757

Water solubility: virtually insoluble

Solubility in other solvents

No data available

Partition coefficient:

No data available

Viscosity / kinematic: 18,6 mm²/s ASTM D 7042

(at 100 °C)

Vapour density:

Evaporation rate:

No data available

No data available

9.2. Other information

No data available

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

# 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

# 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

# 10.5. Incompatible materials

Reacts with: Oxidizing agents, strong. Acid.

according to Regulation (EC) No 1907/2006

### **ADDINOL RACING 4T 15W-50**

Revision date: 30.09.2020 Product code: 721058 Page 6 of 8

# 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

Irritant effect on the eye: irritant.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Specific effects in experiment on an animal

No data available

# **SECTION 12: Ecological information**

# 12.1. Toxicity

No data available

Mixture not tested.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d] Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	Acute fish toxicity	LC50 >1.000 mg/l	96 h		
	Acute algae toxicity	ErC50 >100 mg/l	72 h		

# 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

according to Regulation (EC) No 1907/2006

### **ADDINOL RACING 4T 15W-50**

Product code: 721058 Revision date: 30.09.2020 Page 7 of 8

### 12.3. Bioaccumulative potential

No data available

### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

# 12.6. Other adverse effects

No data available

### **Further information**

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

#### **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

# List of Wastes Code - residues/unused products

OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

### **SECTION 14: Transport information**

Land transp	ort (ADR/	KID)
-------------	-----------	------

14.1. UN number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4 Packing group:	_

Inland waterways transport (ADN)	
14.1. UN number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Marine transport (IMDG)	
14.1. UN number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number:</u>	-

14.2. UN proper shipping name:

according to Regulation (EC) No 1907/2006

### **ADDINOL RACING 4T 15W-50**

Revision date: 30.09.2020 Product code: 721058 Page 8 of 8

14.3. Transport hazard class(es):
14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

#### Other applicable information

No dangerous good in sense of these transport regulations.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

Entry 30: phenol, (tetrapropenyl) derivatives

### **National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

### **Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)